

Msuper X 100V Specification	
Appearance	
Dimension	L*W*H=490*440*560
Dimension(footrests folded)	L*W*H=490*230*560
Wheel diameter	482mm
Footrest height	165mm
Net Weight	20.5/23.5/23.5kg
Performance	
Safe cruising speed	20km/h
Cruising range	120km in real test(70kg rider at 20km/h)
Max climbing	20°in real test(90kg rider)
Max load	100kg
Motor	2000Watt
Battery	1230wh
Hardware	
Battery	Sanyo
Charger	100V/3A
Charging duration	4.5h
Protection	
Over speed alarm	30km/h ,2beeps/sec;
Incline alarm	Automatically shut off to protect rider when wheel is leaning at 35° from forward to backward direction ,45° from left and right direction
Speed alarm	First class alarm: 2 beeps/sec
	Second class alarm: 3beeps/sec
	80% motor output, 5 beeps/sec
Other alarm	low voltage, <7.2km/h, 2 beeps/sec
	low voltage, >7.2km/h, 2beeps/2 sec
	low voltage, >14.4km/h, 3 beeps/2 sec
	hall malfunction, 2 beeps per 0.5 sec
	PCB overheat, 2 beeps(short)
	extreme low voltage, 1 beep/sec, totally 5 beeps
	fall down, 1 beep/sec, totally 5 beeps
over voltage, 3 beeps/2sec	
Main board overheat alarm	Main board temperature>80℃ ,urgent beeps from the wheel, footrests start lifting backward.
Special feature	
Calibration	Use APP ,to set horizontal level or any footrest angle at your choice
Package	
One charger, one GotWay	
Color available	
Black	